

GEL Long Life Series

Model	Voltage	Capacity	Hour Rate	Dimension LxWxHxTH		Weight		Terminal Type	Polarity
	(V)	(Ah)		mm	inch	Kg	Lbs		
OT33-12(GEL)/CL	12	33	20HR	194*132*170*174	7.64*5.2*6.69*6.85	10.35	22.82	T1	C
OT33-12(GEL)/CL	12	33	20HR	195*130*158*180	7.68*5.12*6.22*7.09	10.35	22.82	B8	C
OT40-12(GEL)/CL	12	40	10HR	196*166*173*173	7.72*6.54*6.81*6.81	13.90	30.64	T1	D
OT55-12(GEL)/CL	12	55	10HR	228*138*205*222	8.98*5.43*8.07*8.74	16.80	37.04	B2	C
OT55-12(GEL)/CL	12	55	10HR	228*137*211*214	8.98*5.39*8.31*8.43	16.80	37.04	T1	C
OT65-12(GEL)/CL	12	65	10HR	350*167*173*173	13.78*6.57*6.81*6.81	22.90	50.49	T3	D
OT100-12(GEL)/CL	12	100	10HR	333*173*216*222	13.11*6.81*8.5*8.74	32.50	71.65	W	C
OT100-12(GEL)/CL	12	100	10HR	333*173*216*222	13.11*6.81*8.5*8.74	32.50	71.65	T3	C
OT120-12(GEL)/CL	12	120	10HR	406*172*208*237	15.98*6.77*8.19*9.33	38.00	83.78	T2	C
OT150-12(GEL)/CL	12	150	10HR	484*170*241*241	19.06*6.69*9.49*9.49	47.20	104.06	T3	C
OT150-12(GEL)/CL	12	150	10HR	484*170*241*241	19.06*6.69*9.49*9.49	47.20	104.06	W	C
OT180-12(GEL)/CL	12	180	10HR	522*239*217*222	20.55*9.41*8.54*8.74	60.30	132.94	T3	E
OT200-12(GEL)/CL	12	200	10HR	522*239*217*222	20.55*9.41*8.54*8.74	63.30	139.55	W	E
OT200-12(GEL)/CL	12	200	10HR	522*239*217*222	20.55*9.41*8.54*8.74	63.30	139.55	T3	E